

PRODUCT-DETAILS

SPL25/25M

OIL RES UR LIQ.TIGHT NC25 25MT BLK



General Information

Extended Product Type	SPL25/25M
Product ID	7TCA296030R0193
EAN	5020963000263
Catalog Description	OIL RES UR LIQ.TIGHT NC25 25MT BLK
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering

EAN	5020963000263
UPC	786210247052
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	25 m
----------------------------	------

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Covering

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece
Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	16 in 406 mm
Package Level 2 Width	17 in 432 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL25/25M
Instructions and Manuals	SPL25/25M
Declaration of Conformity - CE	9AKK107492A9618

Classifications

UNSPSC	39131706
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

