

Weatherproof Switched Isolator IP66



- Range features:**
- Degree of protection IP66 prevents dust and powerful water jets
 - Complies to outdoor applications
 - Enclosure made of high quality PC materials and high temperature insulation
 - Resistance to Ultra Violet (UV) radiation and anti-corrosion
- Isolator:**
- High reliability with 4500 A rated short-circuit making capacity for isolators
 - Complete accessories for easy installation

Technical Specification

Standard Specifications	IEC 60947-3 (Third Edition) + A1:2012 + A2:2015
Number of poles	2P & 4P
Rated operational current	20 A, 32 A, 45 A, 63 A
Rated operational voltage	240 V/440 V
Rated insulation voltage	630 V
Rated impulse withstand voltage	2.5 KV 1.2/50 µs
Rated frequency	50/60 Hz
Rated utilization	AC-23 A
Rated making capacity	3 Ie
Rated breaking capacity	3 Ie
Rated short-time withstادن current	15 Ie for 1 s
Rated short-circuit making capacity	4500 A
Pollution degree	3
Degree of protection	IP66

Ordering details

Stock code	Type	Description
2TCZ751006R0001	WSD220CL	20 A 2P Switch-Isolator
2TCZ751006R0002	WSD232CL	32 A 2P Switch-Isolator
2TCZ751006R0003	WSD245CL	45 A 2P Switch-Isolator
2TCZ751006R0004	WSD263CL	63 A 2P Switch-Isolator
2TCZ751006R0005	WSD420CL	20 A 4P Switch-Isolator
2TCZ751006R0006	WSD432CL	32 A 4P Switch-Isolator
2TCZ751006R0007	WSD445CL	45 A 4P Switch-Isolator
2TCZ751006R0008	WSD463CL	63 A 4P Switch-Isolator

Dimensions

