

Product data sheet

Characteristics

ER6482

Easy Rack 600mm/24U/800mm , with Roof, Side panel, castors, feet and 4 Brackets, No Bottom, black



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	<ul style="list-style-type: none"> Baying hardware Key(S) Keyed-alike doors and side panels Leveling feet Mounting hardware Pre-installed casters Side panels
--------------------	--

Physical

Maximum mounting depth	64.14 Cm
Number of rack unit	24U
Minimum mounting depth	19.05 Cm
Marking	<ul style="list-style-type: none"> 18 gauge front door 19 gauge rear door 16 gauge post 14 gauge EIA mounting rail
Colour	Black
Depth	80 Cm
Rack width	19"
Height	119.8 Cm
Net weight	68.4 Kg
Permanent permissible load	<ul style="list-style-type: none"> 1199.75 Kg static 599.65 Kg
Width	60 Cm

Conformance

Standards	<ul style="list-style-type: none"> UL 2416 UL 60950-1 EIA-310E
-----------	---

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Weight	74 Kg
Package 1 Height	133 Cm
Package 1 width	85 Cm
Package 1 Length	65 Cm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Product Life Status : **Commercialised**