



Overview

Presentation	UPS management SmartSlot Card which supports the UPSLink protocol for SMT, SMX and SURTD Smart-UPS.
Lead time	Usually in Stock

General

Provided equipment	RS-232 configuration cable User manual
--------------------	---

Physical

Colour	Black
Depth	11.4 Cm
Height	3.8 Cm
Net weight	0.08 Kg
Width	12.1 Cm



Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-5...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 M

Packing Units

Package 1 Weight	0.34 Kg
Package 1 Height	5.1 Cm
Package 1 width	23.5 Cm
Package 1 Length	15.9 Cm
SCC14	10731304283215

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : Commercialised
