



Overview

Presentation	An industry-standard server rack ready for medium to high-density environments with height designed to easily fit through standard doorways. A deeper-rack design provides enough rack mounting space for even the deepest devices and still plenty of room for vertically mounting Rack PDUs and cable management. 48U height allows for an additional 6U of rack mounting space maximizing u-space per rack footprint.
Lead time	Usually in Stock

General

Provided equipment	Baying hardware Key(S) Leveling feet Mounting hardware Pre-installed casters Side panels
--------------------	---

Physical

Maximum mounting depth	105.99 Cm
Number of rack unit	48U
Minimum mounting depth	19.1 Cm
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Colour	Black
Depth	120 Cm
Rack width	19"
Height	225.8 Cm
Net weight	149.55 Kg
Permanent permissible load	1020.58 Kg dynamic 1700.97 Kg static
Width	60 Cm




Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Packing Units

Package 1 Weight	165.45 Kg
Package 1 Height	238.5 Cm
Package 1 width	75.2 Cm
Package 1 Length	133.4 Cm
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Take-back	Take-back program available

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Product Life Status : Commercialised
