

Advanced

OdourGuard

HVAC Odour Eliminator



A general purpose, 360° protection against odour and unpleasant smell from HVAC equipment. This odour absorbing formula eliminates odours and noxious smells created by smoke, mildew, pets and organic acids.

Features & Benefits

- Triple blend of odour inhibitors and eliminators to ensure 360° protection.
- Removes general odour, cigarette smoke, sweaty gym smells, pet odour, commercial kitchen smells, garlic and onion smell at homes trapped in air handling units.
- Self-reactivates on AC filters, after drying, with high humidity or water.
- Also useful for engineers' shoes and vehicles.
- Formulated to be compatible with all surfaces including metal, alloys, plastic, ceramics, fabric, rubber, etc.
- Forms a transparent protective layer over the surface.
- Fast, effective, and long-lasting protection using organo-crystals (ISO 18184).
- Enables pre-impregnation of surfaces and filters to effect an anti-odour function.
- Non-toxic and biodegradable – ideal for household and industrial applications.
- Does not interfere with existing perfume components in Smelly Jellys.

Suitability

- New and old AC, air handling units, extractor fans and duct work.
- Ideally used after servicing HVAC.
- Use with or without Advanced Cleaning products.
- Compatible with all system materials including steel, copper, aluminium, alloys, plastic, ceramics, fabric, rubber, etc.

Areas for Use

- Offices, vehicles, restrooms, kitchens, homes.
- Extensions to existing systems within the settings above like sinks, toilets and carpets.
- 1L treats an approximate surface area of 10m².



Product Details

Packaging

Bottle = 1L trigger action	Pallet = 45 boxes
128mm x 82mm x 332mm	1200mm x 1000mm x 1191mm
1.11kg	413.11kg

Box = 8 x 1L
341mm x 172mm x 347mm
9.18kg

Health & Safety

Consult SDS for full list of hazards. This product is not classified as hazardous under any use condition and hence ADR unrestricted. Product could be shipped over night with any courier.

Directions for Use

- No need to isolate electrics. Deal for application as part of a regular maintenance programme.
- Air Conditioners and ductwork – Turn AC into Cooling mode (<20°C). Spray product directly into the AC air intake vent and fan system. Wait 5 minutes before switching AC to original setting.
 - General surfaces – Spray and wipe down affected area with a cloth.
 - Toilets, showers, restrooms, and sinks – Spray directly into the drainage receptacle as frequently as required to maintain a fresh environment.
 - Carpets – spray directly onto affected area after vacuuming. Dab with dry cloth to remove excess product.

Storage

- Shelf life = 24 months in original unopened containers.
- Store in original container away from frost in a dry area.

aspenpumps.com

an ASPEN PUMPS GROUP company