

Catalogue No: **800FP-MT44**

PUSHBUTTON 22.5mm PLASTIC E-STOP 40mm

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F
Pushbuttons and Pilot Lights > 800F Emergency Stop Operators > 800F Emergency Stop Operators Only



Representative Photo Only
(actual product may vary based on configuration selections)

PUSHBUTTON 40MM MUSHROOM HEAD TWIST /RELEASE RED

- The 800F line of 22.5 mm push buttons is designed and manufactured to demanding performance specifications to ensure you receive optimized durability and performance.
- 800FP operators are made of industrial grade thermoplastic for superior chemical resistance.
- 800FM operators are constructed of tough die cast zinc alloy, finished with chromate plating that can be used in the most arduous applications.

SPECIFICATIONS

Product Series	800FP
Component Type Pushbutton and Pilot Lights	E-Stop
Operator Type	E-Stop, Mushroom Head
Operator Action	Twist to Release
Diameter, Operator	40
Colour, Operator	Red
Material, Operator	Plastic
Material, Bezel	Glass-Filled Nylon / PA6 / PA66 (Polyamide 6)
Coupling Plate Included	No
Tightening Torque, Nominal	1.7
Material, body / housing	Plastic
Mounting	22.5mm Mounting Hole
Contact Block Included	No
Illuminated	No
Mechanical service life	300000
RoHS Approved	Yes
Operating temperature, max	70
Operating temperature, min	-25
Storage temperature, max	85
Storage temperature, min	-40
Relative humidity, min	50
Relative humidity, max	95
Shock Acceleration (Max.)	100
Shock Duration (Max.)	11
Vibration Acceleration (Max.)	10
Vibration Displacement (Peak to Peak Max.)	1.52
Vibration Frequency, Operational (Max.)	2000

Catalogue No: **800FP-MT44**

PUSHBUTTON 22.5mm PLASTIC E-STOP 40mm

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F
Pushbuttons and Pilot Lights > 800F Emergency Stop Operators > 800F Emergency Stop Operators Only



Vibration Duration (Max.)	180
Standards Compliance	NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 IEC 60947-1 ISO 13850
Certifications	UR UL CSA CCC CE RoHS
Shipping Approvals	ABS (American Bureau of Shipping)

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-