



PILOT LIGHT HEAD YELLOW

- The 800F line of 22.5 mm push buttons is designed and manufactured to demanding performance specifications to ensure you receive optimized durability and performance.
- 800FP operators are made of industrial grade thermoplastic for superior chemical resistance.
- 800FM operators are constructed of tough die cast zinc alloy, finished with chromate plating that can be used in the most arduous applications.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Pushbutton and Pilot Lights	Pilot Light
Diameter, lens	29.6 mm
Colour, Lens	Yellow
Material, Lens	Polyamide
Material, Bezel	Glass-Filled Nylon / PA6 / PA66 (Polyamide 6)
Material, body / housing	TP (Thermoplastic)
Tightening Torque, Nominal	1.7 Nm
Wire / Conductor Size (Min)	0.75 mm ²
Lamp Module Included	No
Mounting	22.5mm Mounting Hole
Dielectric Strength	2.5kV for 1 minute
RoHS Approved	Yes
CE Marked	Yes
Operating temperature, max	70 °C
Operating temperature, min	-25 °C
Storage temperature, max	85 °C
Storage temperature, min	-40 °C
Relative humidity, min	50 %RH
Relative humidity, max	95 %RH
IP rating	IP66
Shock Acceleration (Max.)	100 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	10 g
Vibration Displacement (Peak to Peak Max.)	1.52 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Vibration Duration (Max.)	180 min

Catalogue No: **800FP-P5**

PILOT LIGHT 22.5mm PLASTIC OPERATOR ONLY YELLOW

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F Pushbuttons and Pilot Lights > 800F Pilot Lights > 800F Pilot Light Operators Only



Standards Compliance

NEMA ICS-5
UL 508
EN 60947-1
EN 60947-5-1
EN 60947-5-5
IEC 60947-1
ISO 13850

Certifications

UR
UL
CSA
CCC
CE
RoHS

Shipping Approvals

ABS (American Bureau of Shipping)

REFERENCES

IECEX Certificate -

Supplier Declaration of Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: [800FPP5_Manufacturer Datasheet](#)

Manufacturer Catalogue & Product Selection: [800FPP5_Manufacturer Product Selection Guide](#)

Dimension Diagram