



METAL LATCH

- The 800F line of 22.5 mm push buttons is designed and manufactured to demanding performance specifications to ensure you receive optimized durability and performance.
- 800FP operators are made of industrial grade thermoplastic for superior chemical resistance.
- 800FM operators are constructed of tough die cast zinc alloy, finished with chromate plating that can be used in the most arduous applications.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Pushbutton and Pilot Lights	Coupling Plate
Compatible Product Series'	800F
Material, body / housing	Zinc Alloy, Die-Cast, Painted
Package Quantity	10
Mechanical service life	10000000 cycles
RoHS Approved	Yes
CE Marked	Yes
Operating temperature, max	70 °C
Operating temperature, min	-25 °C
Storage temperature, max	85 °C
Storage temperature, min	-40 °C
Relative humidity, min	50 %RH
Relative humidity, max	95 %RH
Shock Acceleration (Max.)	100 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	10 g
Vibration Displacement (Peak to Peak Max.)	1.52 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Vibration Duration (Max.)	180 min
Standards Compliance	NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 IEC 60947-1 ISO 13850

Catalogue No: **800F-ALM**

COUPLING PLATE METAL FITS 3 CONTACT BLOCKS ACROSS

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F
Pushbuttons and Pilot Lights > 800F Contact Blocks and Coupling Plates > Coupling plates



Certifications	UR UL CSA CCC CE RoHS
Shipping Approvals	ABS (American Bureau of Shipping)

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	800F_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	800F_Manufacturer Catalogue