



## PROTECTIVE RING

- The 800F line of 22.5 mm push buttons is designed and manufactured to demanding performance specifications to ensure you receive optimized durability and performance.
- 800FP operators are made of industrial grade thermoplastic for superior chemical resistance.
- 800FM operators are constructed of tough die cast zinc alloy, finished with chromate plating that can be used in the most arduous applications.

Representative Photo Only  
(actual product may vary based on configuration selections)

### SPECIFICATIONS

Component Type Pushbutton and Pilot Lights	Accessories - General
Compatible Product Series'	800F
Details, compatible product series	for use with illuminated/non-illuminated 2-position maintained and illuminated/non-illuminated 3-position mushroom operators (30 mm and 40 mm only)
Colour	Grey
Material	Metal
Package Quantity	1
RoHS Approved	Yes
CE Marked	Yes
Operating temperature, max	70 °C
Operating temperature, min	-25 °C
Storage temperature, max	85 °C
Storage temperature, min	-40 °C
Relative humidity, min	50 %RH
Relative humidity, max	95 %RH
Shock Acceleration (Max.)	100 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	10 g
Vibration Displacement (Peak to Peak Max.)	1.52 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Vibration Duration (Max.)	180 min

Catalogue No: **800F-AMRG**  
**RING PROTECTIVE METAL FOR 40mm MUSH OPERATORS**

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F  
Pushbuttons and Pilot Lights > 800F Accessories > Protective guards



Standards Compliance	NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 IEC 60947-1 ISO 13850
Certifications	UR UL CSA CCC CE RoHS
Shipping Approvals	ABS (American Bureau of Shipping)

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-