

Stainless Outdoor Lighting

BRUSHED STAINLESS STEEL, POLYCARBONATE LENS



FS4227



FS6189



FS4996



FS4997

E27

FLUORESCENT SBF80-13EWW



- **60 lm/W** • 780 total lm
- 13Watts • 2,700K • CRI>80 • 70° Beam

LED R80-10EWW



- **70 lm/W** • 700 total lm
- 10Watts • 3,000K • CRI>81 • 120° Beam

E27 **MAX.**
60W **IP**
23 **304**
Stainless
Steel

FS4227

- 230mmH x 100mmW x 115mmD

E27

FLUORESCENT SBF3U-15EWW



- **60 lm/W** • 900 total lm
- 15Watts • 2,700K • CRI>80

E27 **MAX.**
60W **IP**
23 **304**
Stainless
Steel

FS6189

- 260mmH x 90mm sq
- Mounting base 90mm sq
- Use only with Self-Ballasted Fluorescent

E27 **MAX.**
15W **IP**
44 **304**
Stainless
Steel

FS4996

- 650mmH x 60mmØ
- Mounting flange 100mmØ
- Use only with Self Ballasted Fluorescent

GU10

HALOGEN GU10-35-A



- **10 lm/W** • 350 total lm • Dimmable
- 35Watts • 3,000K • CRI>100 • 36° Beam

LED GU10-HPLED-WH



- **60 lm/W** • 300 total lm
- 5Watts • 4,000K • CRI>80 • 30° Beam

E27 **MAX.**
15W **GU 10** **MAX.**
35W **IP**
44 **304**
Stainless
Steel

FS4997

- 340mmH x 62mmØ
- Top light only for Self Ballasted Fluorescent use
- Down light uses GU10 bulb
- Base 104mmH x 43mmW

"Refer to Material selection and Maintenance"
Warranty not valid for corrosive environments