

**CAT III
500V**



T2751 - Digital Insulation Tester 250, 500 & 1000V

HOUSING

Compact rugged housing with soft rubber boot

STRAPS FIXED TO STUDS

on rubber boot for easy to use position during use

WARNING FOR LIVE LINE VOLTAGE

DATA HOLD
Freezes display

COLOUR CODED

AUTO POWER OFF



CAT III 500V

DIGITAL DISPLAY
Large digits at least one decimal point e.g. 1.0μΩ on 1000V

POWER ON INDICATION

PUSH BUTTON WITH LOCK
Timer 3 to 5min

ZERO ADJUST FOR LOW Ω

SELECTOR SWITCH
AC V (0-600V)
High Ω (250, 500 & 1000V)
Low Ω (20, 200 & 200 Ω)

FEATURE	RANGE	ACCURACY
Insulation	0 to 20MΩ (250V DC ± 10%)	± 1.5% ± 5d
	0 to 200MΩ (500V DC ± 10%)	± 2.5% ± 3d
	0 to 2000MΩ (1000V DC ± 10%)	± 5½ ± 5d
Continuity	20/ 200/ 2000Ω	± 1.5% + 3d
AC Voltage	0 to 600V AC; 40 –120Hz	± 1.5% ± 3d
Voltage	90V DC, 70V AC for Visual Indication,	
Warning	24V for Buzzer	

ORDERING INFORMATION

Part No: **T2751**

The unit comes in a soft pouch with holster, batteries, spare fuse, leads & crocodile clips, manual and shoulder strap.

Batteries: 6 x 1.5 V AA

Fuse: 0.5 A (5 x 20mm)

Size: L200 x W85 x T55mm

Weight: 1380g with Batteries

For replacement test leads order AL24.

*Refer to CABAC website cabac.com.au for terms and conditions on warranty.