

T8229 - 5 in 1 Auto Range Digital Multimeter

SENSORS LUX, RH% & SOUND
Located on top

COMPACT RUGGED CASE
Rugged housing with soft boot

MULTIPLE DISPLAY
RH%, + temperature constantly displayed
3 3/4 399 count LCD

MANUAL RANGE SELECTION

RELATIVE MEASUREMENT

TEMPERATURE F° OR C°

HOLD DATA BACK LIGHT

AUTO RANGING

FUSE CURRENT RANGES

CAT III 600V

TEMPERATURE
Measurement type K thermocouple
Measures V, A, Ω , C°, RH%, Lux & sound

FEATURE	RANGE	ACCURACY
AC/DC Voltage	400m/4/40/400/1000V	$\pm 0.7\%$ to 2%
AC/DC Current	400 μ /4000 μ /40m/400mA 10A	$\pm 1.2\%$ to 3%
Resistance	400/4k/40k/400k/4M/4M Ω	$\pm 1.0\%$
Capacitance	50n/500n/5 μ /500 μ /200 μ F	$\pm 3.0\%$
Frequency	10/100/1k/10k/100kHz	$\pm 2.0\%$
Temperature	-20°C ~ 1000°C	$\pm 3.0\%$ or $\pm 20\text{C}, 0^\circ\text{F}$
Humidity	20% ~ 95%RH	$\pm 5.0\text{RH}$
Light	4000Lux/40000Lux	$\pm 5.0\%$
Sound level	40 ~ 100dB	$\pm 5\text{dB}$

ORDERING INFORMATION

Part No: T8229

Each unit is supplied with soft pouch, test leads, thermocouple & adaptor and instruction manual.

Batteries: 3 x AA

Size: L195mm x W92mm x T55mm

Weight: Approx. 400g (including batteries)

For replacement test leads order AL04 or AL28-1.



*Refer to CABAC website cabac.com.au for terms and conditions on warranty.