

METAL UNJACKETED**Features & Benefits**

- Extra flexible electrogalvanised steel conduit - interlocked, unjacketed and helically wound
- Very high temperature rating -20 to +250 Degrees
- High mechanical protection and moisture resistance
- Suitable for tight complex bends and dynamic moving installations

Ordering Information

PART NUMBER	DESCRIPTION
CEFU10-25	Extra Flex 10mm Uncovered 25m
CEFU12-25	Extra Flex 12mm Uncovered 25m
CEFU16-25	Extra Flex 16mm Uncovered 25m
CEFU20-25	Extra Flex 20mm Uncovered 25m
CEFU25-25	Extra Flex 25mm Uncovered 25m
CEFU32-25	Extra Flex 32mm Uncovered 25m
CEFU40-10	Extra Flex 40mm Uncovered 10m
CEFU50-10	Extra Flex 50mm Uncovered 10m
CEFU63-10	Extra Flex 63mm Uncovered 10m



In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.