CHEMTOOLS

A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road St Marys NSW 2760 Australia Ph: 1300 738 250 (Australia) Ph: +61 2 9833 9766 (International) Fax: 02 9623 3670 sales@chemtools.com.au www.chemtools.com.au

TECHNICAL DATA SHEET

FEBRUARY 2015

PRODUCT NAME

R14 Silicone Dielectric Grease Spray

PRODUCT RANGE

Part Number Available Size
CT-R14-400 400g Aerosol
CT-R14-S10-PT10cc Manual Syringe
CT-R14-S30-PT30cc Manual Syringe
CT-R14-500G 500g Jar

CT-R14-500G 500g Jar
CT-R14-1KG 1 Kg Tub
CT-R14-4KG 4 Kg Tub



Refer to SDS for product safety guidelines

R14 Silicone Dielectric Grease Spray

Chemtools® R14 Dielectric Grease Spray is specially formulated to protect, lubricate, and waterproof electrical wiring and components. R14 will extend component operating life, and will shield electrical components from the harmful effects of salt, dirt, and corrosion.

FEATURES AND BENEFITS:

- Resistance to water washout
- High drop point
- High load resistance
- Increase life of belt with regular use
- Remains tacky and is water resistant

APPLICATION:

- Automotive and 4WD repair shops
- Telecommunications
- Defence and Avionics
- Marine and Boat repair
- Electrical services
- Heavy equipment maintenance
- Truck and Farming equipment repairs
- Mining equipment maintenance and repairs

PROPERTIES:

Appearance Smooth Translucent Paste

Drop point +300°C

Water washout: Excellent resistance

Dielectric Strength 37kV

Shelf life: > 2 years after date of manufacture

STORAGE:

Store in closed containers, undercover, in a cool and dry environment.

SAFETY:

Please refer to SDS before use. For industrial use only, please keep out of reach of children. Wear suitable safety gear before use.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.