



CUBPRO-HV

CLEVERTRONICS LP ULTRABLADE PRO RECESSED EXIT



PRODUCT INFORMATION

| | |
|--------------------------|----------------------------------------------------------------------|
| Catalogue Number | CUBPRO-HV |
| MIC | AUA02810020002 |
| Description | LP Premium Ultrablade Pro Blade Recessed Exit |
| Construction | PC/ABS Body with PC Diffuser |
| Mounting | Recessed ceiling |
| Dimensions L x W x H | 317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate) |
| Ceiling Hole Cut-Out | 350mm x 48mm |
| Minimum Ceiling Depth | 80mm |
| Weight | 1.1kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Iron Phosphate 3.2V 1100mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All pictograph directional inserts included in the box |
| Lamp (s) | 12 x Duris E3 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.8 Watts (Standby), 4.2 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=E6.3 C90=E6.3 |
| Viewing Distance | 24M |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|----------------------------------|-----------------------------------------------------------------|
| 1550105 | BATT:LP 3.2V 1100mAh 260mm lead,no BRKT. |
| 8002178 | PCA:UBP LED strip PCB Assy (CT10602-Dx) |
| AUM02870020002 CUBPRO-CKIT-HV | Ultrablade Pro, Control Only, CT10622, LP, HV (incl. Hive node) |
| 8003191 | PCA: RF Node CT10678-A12 Int Antenna LLPro |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.