

Clevertronics

Lifelight PRO Emergency with IP65 Lamp Head: LLIFE-PRO-WP



Lifelight PRO WP Lamp Head

PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-WP
Description	Lifelight PRO, High Performance, Recessed emergency light with IP66/67 Head
Mounting	Surface Mount
Dimensions L x W x H	122mm x 120mm x 75mm (IP66/67 Lamp head enclosure)
Ceiling hole cut-out	NA
Operating Mode	Non-Maintained
Testing System	Manual Test Button
Ballast	Electronic
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V
Power Consumption	0.8W (standby)
IP Rating	IP66/67 Lamp Head Enclosure
Impact Rating	IK08 (Lamp Enclosure)
Operating Temperature	0°C to 40°C (ambient for battery and control gear) -40°C to 40°C (ambient for weatherproof lamp head)
AS2293 Classification	C0=D40, C90=D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery, 3.3 Volt 5Ah Li-ion
8002390	Driver, PCA: ZONEWORKS Compatible
1100830	2 x 3W LED Round Head Assembly-White