



## NIFTY-SM

Nifty Lifelight Emergency, Surface Mount, Trade Series



### PRODUCT INFORMATION

Part Number	NIFTY-SM
MIC	AUD03510060001
Description	Nifty Lifelight Emergency, Surface Mount, Trade Series
Construction	PC/ABS
Mounting	Recessed mount
Dimensions	140mm Head Diameter 77mm Height
Weight	0.5kg
Operating Mode	Non-maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	4 x LED
Operating Voltage	240V AC; 50Hz
Power Consumption	0.5 Watts (Standby), 1.6 Watts (Max)
Power Factor (High)	0.352
Inrush Current	26.6A / 47.2 $\mu$ s
Supply Current	20.51mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560106	BATT:Eco Lith 3.2V 1.5Ah 80mm lead, no BRKT

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.