

Product data sheet

Characteristics

3025CSGZ

Connected Socket, Iconic, Zigbee default mode, Twin horizontal, 10 A, 240 V, Grid



Main

Range compatibility	Wiser hub Clipsal mounting bracket Clipsal wall box
Product brand	Clipsal
Range	Iconic
Product or component type	Socket-outlet

Complementary

Device presentation	Complete product
Socket-outlet type	Twin switched socket-outlet
[Ue] rated operational voltage	240 V AC 50 Hz
Colour tint	White
Surface finish	Matt
Local signalling	LED
Control type	Rocker on/off switching By mobile application
Software name	Wiser by SE App
Module configuration	Programmed with touch switch
Rated current	10 A
Technology type	Zigbee default Bluetooth low energy
Memory description	Backup memory - date and time for 6 h Backup memory - program for indefinite period
Material	Plastic
Type of installation	Indoor installation

Environment





IP degree of protection	IP20
Relative humidity	5...90 % non-condensing
Standards	AS/NZS 3112 safety AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	202 g
Package 1 Height	5.4 cm
Package 1 width	9.5 cm

Package 1 Length	14.1 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	4.5 kg
Package 2 Height	22.7 cm
Package 2 width	26.4 cm
Package 2 Length	33.8 cm
Unit Type of Package 3	PAL
Number of Units in Package 3	960
Package 3 Weight	238 kg
Package 3 Height	95 cm
Package 3 width	114 cm
Package 3 Length	114 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information