

Main	
Range	Clipsal Iconic
Product or component type	USB charger
[Ue] rated operational voltage	220/240 V AC 50 Hz
Integrated connection type	3 USB 2.0 type A 5 V DC, maximum load current: 2.1 A
Maximum load current with 2 outputs used simultaneously	4.5 A

Complementary

1	
Device mounting	Flush
Device presentation	Complete product
Colour tint	Vivid white (VW)
Surface finish	Matt Textured
Fixing mode	By screws
Type of packing	Polybag
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-550 °C
Relative humidity	1595 %
Protection type	Short time short-circuit protection
Number of terminals	3 screw terminal
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	4 x 2.5 mm² for stranded cable(s) 4 x 2.5 mm² for flexible cable(s) 4 x 2.5 mm² for rigid cable(s)
Wire stripping length	16 mm
Height	78 mm
Width	120 mm
Depth	70 mm
Embedding depth	35 mm

Environment

Product certifications	RCM	
Electrical insulation class	Class II	
IK degree of protection	IK04	
IP degree of protection	IP21	

Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	Product Environmental Profile