



Main

Range	Clipsal Iconic
Product or component type	Timer
Device presentation	Mechanism

Complementary

Device mounting	Flush
Actuator	Push-button
Fixing mode	Clip-in
Colour tint	Vivid white
Surface finish	Matt
Connections - terminals	4 screw terminals
Type of packing	Box
Sale per indivisible quantity	1
Time delay	1...86400 s (24 h) adjustable
Remote control type	Push-button Wiser room application
[Ie] rated operational current	10 A
[Ue] rated operational voltage	240 V AC 50 Hz
Load type	LED lighting 10 A Incandescent lamp 10 A Low voltage halogen lamp with iron core transformer 10 A Low voltage halogen lamp with electronic transformer 10 A Fluorescent lamp 10 A Compact fluorescent lamp 10 A Resistive 15 A
Power range	> 0 W
Derating factor	Number of devices 1 10 A without derating Number of devices 2 7.5 A with derating Number of devices 3 6.5 A with derating
Operating distance	30 m
Control signal type	Controllink
Connections - terminals	Screw terminals
Number of terminals	4
Wiring configuration	3 wires with neutral
Screwdriver shape	Philips Square drive no 1 (SQ1)
Local signalling	LED indicator warm white
Material	PC (UL94 V-2) for top PC MAS056 (UL94 V-2) for bottom
Height	24 mm
Width	48 mm
Depth	55 mm
Embedding depth	52 mm

Environment

ambient air temperature for storage	0...60 °C
ambient air temperature for operation	0...45 °C
relative humidity	0...90 %

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1713 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available