

Product data sheet

Characteristics

O3015T-BK

Switched socket outlet, Iconic Outdoor, Single with timer, 10 A, 250 V, Black



Main

Range of product	Iconic
Product or component type	Switched socket
Product brand	Clipsal
Device presentation	Complete product
Colour	Black
Colour code	BK
Software name	Wiser by SE App
Switch application	On/off switching
Technology type	Bluetooth low energy Zigbee
Memory description	Backup memory Backup memory
Memory usage	Date and time Program
Outlet poles configuration	1P + E

Complementary

Control type	ON/OFF button Rocker By mobile application
Pin number	3
Number of power socket outlets	1
Socket-outlet type	Single socket-outlet
Fixing mode	By screws By clipping locks
Local signalling	Without light indicator
Device mounting	Surface Wall mounted
Mounting position	Horizontal
Material	PC (polycarbonate) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Surface finish	Matt
Type of installation	Outdoor
[Ue] rated operational voltage	240 V AC
Network frequency	50 Hz
[In] rated current	10 A
Clamping connection capacity	3 x 2.5 mm ² 2 x 4 mm ²
Connections - terminals	3 screw terminals
Depth	82 mm
Height	85 mm
Width	115.5 mm


Environment

IP degree of protection	IP54
Product certifications	RCM
Electrical durability	12000 cycles
Standards application	Safety Safety EMC Radio
Ambient air temperature for storage	0...60 °C
Standards	AS/NZS 3112
Relative humidity	10...95 %
Ambient air temperature for operation	0...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	332.0 g
Package 1 Height	10.1 cm
Package 1 width	11.9 cm
Package 1 Length	8.9 cm
Unit Type of Package 2	BB2
Number of Units in Package 2	25
Package 2 Weight	9.3 kg
Package 2 Height	33.5 cm
Package 2 width	26.1 cm
Package 2 Length	45.9 cm
Unit Type of Package 3	P06
Number of Units in Package 3	300
Package 3 Weight	120.1 kg
Package 3 Height	105 cm
Package 3 width	60 cm
Package 3 Length	80 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Halogen content performance	Halogen free plastic parts product