

FLORYN FLA

Exterior Lighting / Flood Light

FLORYN FLA-FLA150G15K



DAVISLIGHTING

Features

Die-cast aluminium body
Low energy consumption
Rubber supply cable
Fast turn-on, near zero maintenance
Adjustable mounting bracket

Applications

Plazas
Courtyards
Factories, warehouses
Gardens, parks
Sporting venues

Standards

Manufactured under ISO 9001:2015 to standards
IEC/AS/NZS 60598.1
IEC/AS/NZS 60598.2.5
IEC/AS/NZS CISPR 15

Mounting Methods



Trunnion



FLORYN FLA

Exterior Lighting / Flood Light



Specifications

Model	FLA150G15K
Nominal Power (W)	150
Input Voltage (V)	220 - 240 VAC 50 / 60 Hz
Luminous Flux (lm)	14400
Efficacy (lm/W)	95
CRI (Ra)	>70
Power Factor	>0.95
CCT (K)	5000
Rated Life L70B50 (hr)	30000
Ambient Temp. ta (°C)	40
Weight (kg)	3.75

Packaging Details


Model	FLA150G15K
Product Carton Qty per box (pc)	1
Product Carton Dimension (mm)	360 x 53 x 325
Master Carton Qty per box (pc)	4
Master Carton Dimension (mm)	375 x 235 x 350
Master Carton Weight (kg)	17.1

FLORYN FLA


Exterior Lighting / Flood Light



Lighting Data



Dimensions



davislighting.com



davislighting.com.au

All photometric and electrical data published are of $\pm 10\%$ tolerance. Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a suitably qualified person. Application images are indicative only and may not contain actual Davis product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance.