



aux.contact module, 4-poles, front



Powering Business Worldwide™

Part no. **DILM150-XHI22**  
 Article no. **277950**  
 Catalog No. **XTCEXFBG22**

### Delivery programme


Product range  
 Accessories  
 Description  
 Function  
 Pole  
 Connection technique  
 Rated operational current  
 AC-3  
 Conventional free air thermal current, 3 pole, 50 - 60 Hz  
 Open  
 at 60 °C  
 AC-15  
 220 V 230 V 240 V  
 380 V 400 V 415 V  
 Contacts  
 N/O = Normally open  
 N/C = Normally closed  
 Mounting type  
 Contact sequence

$I_{th} = I_e$  A  
 $I_e$  A  
 $I_e$  A

Accessories  
 Auxiliary contact modules with interlocked opposing contacts for standard applications  
 4 pole  
 Screw terminals

16  
 6  
 4

2 N/O  
 2 NC  
 Front fixing



For use with

DILM40...  
 DILM50...  
 DILM65...  
 DILM72...  
 DILM80...  
 DILM95...  
 DILM115...  
 DILM150...  
 DILM170...  
 DILMP63...  
 DILMP80...  
 DILMP125...  
 DILMP160...  
 DILMP200...  
 Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILM 7 - DILM32  
 Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

### Instructions

### Approvals

Product Standards  
 UL File No.  
 UL Category Control No.  
 CSA File No.  
 CSA Class No.  
 North America Certification  
 Specially designed for North America

IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking  
 E29184  
 NKCR  
 012528  
 3211-03  
 UL listed, CSA certified  
 No

### Electrical specifications for standard auxiliary contacts

Interlocked opposing contacts within an auxiliary contact module (to IEC 60947-5-1 Annex L)  
 N/C contact (not late-break contact) suitable as a mirror contact (to IEC/EN 60947-4-1 Annex F)  
 Rated impulse withstand voltage

Overvoltage category/pollution degree

Rated insulation voltage

Rated operational voltage

Safe isolation to EN 61140

between coil and auxiliary contacts

between the auxiliary contacts

|           |         |                  |
|-----------|---------|------------------|
|           |         | Yes              |
|           |         | DILM40 - DILM170 |
| $U_{imp}$ | V<br>AC | 6000             |
|           |         | III/3            |
| $U_i$     | V<br>AC | 690              |
| $U_e$     | V<br>AC | 500              |
|           | V<br>AC | 440              |
|           | V<br>AC | 440              |

|                                                           |                |                |                                                                                                                 |
|-----------------------------------------------------------|----------------|----------------|-----------------------------------------------------------------------------------------------------------------|
| Rated operational current                                 |                | A              |                                                                                                                 |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                |                |                                                                                                                 |
| Open                                                      |                |                |                                                                                                                 |
| at 60 °C                                                  | $I_{th} = I_e$ | A              | 16                                                                                                              |
| AC-15                                                     |                |                |                                                                                                                 |
| 220 V 230 V 240 V                                         | $I_e$          | A              | 6                                                                                                               |
| 380 V 400 V 415 V                                         | $I_e$          | A              | 4                                                                                                               |
| 500 V                                                     | $I_e$          | A              | 1.5                                                                                                             |
| DC current                                                |                |                |                                                                                                                 |
| DC L/R 15 ms                                              |                |                |                                                                                                                 |
| 24 V                                                      | $I_e$          | A              | 10                                                                                                              |
| 60 V                                                      | $I_e$          | A              | 6                                                                                                               |
| 110 V                                                     | $I_e$          | A              | 3                                                                                                               |
| 220 V                                                     | $I_e$          | A              | 1                                                                                                               |
| Control circuit reliability                               | Failure rate   | $\lambda$      | $<10^{-8}$ , < one failure at 100 million operations (at $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA) |
| Component lifespan                                        |                |                |                                                                                                                 |
| at $U_e = 230$ V, AC-15, 3 A                              | Operations     | $x 10^6$       | 1.3                                                                                                             |
| Short-circuit rating without welding                      |                |                |                                                                                                                 |
| max. fuse                                                 |                | A<br>gG/<br>gL | 16                                                                                                              |

## Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss8-27-37-13-02 [AKN342009])

|                                               |   |                  |
|-----------------------------------------------|---|------------------|
| Number of contacts as change-over contact     |   | 0                |
| Number of contacts as normally open contact   |   | 2                |
| Number of contacts as normally closed contact |   | 2                |
| Rated operation current $I_e$ at AC-15, 230 V | A | 6                |
| Type of electric connection                   |   | Screw connection |
| Mounting method                               |   | Front fastening  |

## Additional product information (links)

### IL03407034Z (AWA2100-2251) Auxiliary contact

IL03407034Z (AWA2100-2251) Auxiliary contact [ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL03407034Z2010\\_10.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407034Z2010_10.pdf)

<http://de.ecat.moeller.net/flip-cat/?edition=HPLTE&startpage=5.84>

Switchgear of Power Factor Correction Systems [http://www.moeller.net/binary/ver\\_techpapers/ver934en.pdf](http://www.moeller.net/binary/ver_techpapers/ver934en.pdf)

X-Start - Modern Switching Installations Efficiently Fitted and Wired Securely [http://www.moeller.net/binary/ver\\_techpapers/ver938en.pdf](http://www.moeller.net/binary/ver_techpapers/ver938en.pdf)

Mirror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions [http://www.moeller.net/binary/ver\\_techpapers/ver944en.pdf](http://www.moeller.net/binary/ver_techpapers/ver944en.pdf)

Effect of the Cable Capacitance of Long Control Cables on the Actuation of Contactors [http://www.moeller.net/binary/ver\\_techpapers/ver949en.pdf](http://www.moeller.net/binary/ver_techpapers/ver949en.pdf)

Motor starters and "Special Purpose Ratings" for the North American market [http://www.moeller.net/binary/ver\\_techpapers/ver953en.pdf](http://www.moeller.net/binary/ver_techpapers/ver953en.pdf)

Switchgear for Luminaires [http://www.moeller.net/binary/ver\\_techpapers/ver955en.pdf](http://www.moeller.net/binary/ver_techpapers/ver955en.pdf)

Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts [http://www.moeller.net/binary/ver\\_techpapers/ver956en.pdf](http://www.moeller.net/binary/ver_techpapers/ver956en.pdf)

The Interaction of Contactors with PLCs [http://www.moeller.net/binary/ver\\_techpapers/ver957en.pdf](http://www.moeller.net/binary/ver_techpapers/ver957en.pdf)

Busbar Component Adapters for modern Industrial control panels [http://www.moeller.net/binary/ver\\_techpapers/ver960en.pdf](http://www.moeller.net/binary/ver_techpapers/ver960en.pdf)