

Building Wire HT (High Temp.)

Application: For separate earth conductors, switchboard, and control panel wiring. Suitable for glanding.

Conductor: Plain Annealed Copper

Insulation: V90HT PVC Temp: 105°C

Standards: AS/NZS 5000.1, AS/NZS 1125, AS/NZS 3808

Greenstar: Approved **Drum Sizes:** 100m, 500m

ELECTRA Part Number	SIZE	INSULATION Thickness	O.D.	COLOURS
R1005	0.5	0.8	2.4	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, Yellow
R1010	1.0	0.8	2.8	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White,

^{*}Size, Insulation Thickness and O.D. = mm. O.D. ± 10%

Building Wire

Application: For separate earth conductors, switchboard, and control panel wiring. Suitable for glanding.

Conductor: Plain Annealed Copper

Insulation: V90 PVC Temp: 90°C

Standards: AS/NZS 5000.1, AS/NZS 1125, AS/NZS 3808

Greenstar: Approved **Drum Sizes:** 100m, 500m

ELECTRA Part Number	SIZE	INSULATION Thickness	0.D.	COLOURS
SR1015	1.5	0.8	3.1	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White, Yellow
SR1025	2.5	0.8	3.6	Black, Red, Brown, Blue, Pink, Grey, Orange, Violet, White,
SR1040	4	1.0	4.6	Black, Red, Blue, White, Green/Yellow
SR1060	6	1.0	5.1	Black, Red, Blue, White, Green/Yellow
SR1100	10	1.0	6.1	Black, Red, Blue, White, Green/Yellow
SR1160	16	1.0	7.1	Black, Red, Blue, White, Green/Yellow
SR1250	25	1.2	8.9	Black, Red, Green/Yellow
SR1350	35	1.2	10.1	Black, Red, Green/Yellow
SR1500	50	1.4	11.7	Black, Red, Green/Yellow
SR1700	70	1.4	13.6	Black, Red, Green/Yellow
SR1950	95	1.6	15.8	Black, Red, Green/Yellow
SR11200	120	1.6	17.6	Black, Red, Green/Yellow
SR11500	150	1.8	19.5	Black, Red, Green/Yellow
SR11850	185	2.0	21.7	Black, Red, Green/Yellow
SR12400	240	2.2	24.9	Black, Red, Green/Yellow
SR13000	300	2.4	27.7	Black, Red, Green/Yellow
SR14000	400	2.6	30.9	Black, Red, Green/Yellow
SR15000	500	2.8	34.4	Black, Red, Green/Yellow
SR16300	630	2.8	38.4	Black, Red, Green/Yellow

^{*}O.D. ± 10% = mm *Size, Insulation Thickness & O.D. = mm2

electracables.com.au

SYDNEY (02) 8786 5200 MELBOURNE (03) 9706 6819 BRISBANE (07) 3386 9800 PERTH (08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38

^{*}O D + 10% = mm *Size Inculation Thickness & O D = mm