



Club Linkable Batten

Concealable Narrow Strip Batten



FEATURES

- · Super slim design
- · High efficiency SMD chips
- · Fully integrated driver
- · Highly transparent polycarbonate diffuser
- Double insulated polycarbonate body
- · Shatter resistant
- · Fitting colour: White

INCLUDES

- · High efficiency LED Linkable batten
- · 1.2 m flex and plug
- · Mounting brackets and cable connector

INSTALLATION OPTIONS


Surface mounted

APPLICATIONS

- Shops
- Shelves
- Cabinets

WARRANTY

• Five years (subject to terms and conditions)



Part No.	Voltage	Watt.	PF	сст.	Ra	Lumen	Beam Angle	Lifetime L70B50	Size(L*W*H)mm
212015B	220-240V	4W	0.9	3000K	≥80	350lm	160°	25000h	312*24*34
212016B	220-240V	4W	0.9	4000K	≥80	400lm	160°	25000h	312*24*34
212501B	220-240V	4W	0.9	5000K	≥80	400lm	160°	25000h	312*24*34
212017B	220-240V	8.5W	0.9	3000K	≥80	750lm	160°	25000h	562*24*34
212018B	220-240V	8.5W	0.9	4000K	≥80	850lm	160°	25000h	562*24*34
212502B	220-240V	8.5W	0.9	5000K	≥80	850lm	160°	25000h	562*24*34
212019B	220-240V	10.5W	0.9	3000K	≥80	900lm	160°	25000h	912*24*34
212020B	220-240V	10.5W	0.9	4000K	≥80	1050lm	160°	25000h	912*24*34
212503B	220-240V	10.5W	0.9	5000K	≥80	1050lm	160°	25000h	912*24*34
212021B	220-240V	12.5W	0.9	3000K	≥80	1100lm	160°	25000h	1112*24*34
212022B	220-240V	12.5W	0.9	4000K	≥80	1250lm	160°	25000h	1112*24*34
212504B	220-240V	12.5W	0.9	5000K	≥80	1250lm	160°	25000h	1112*24*34

Part No.	Model No.	VEET Status	IPART Status
212015B 212016B 212501B	YKT5BF1V1-L30	Approved VEET No.: 5475	Approved IPART No.: 24143S20-DIYEIJC
212017B 212018B 212502B	YKT5BF1V1-L55	Approved VEET No.: 5475	Approved IPART No.: 24143S20-DIYEIJC
212019B 212020B 212503B	YKT5BF1V1-L90	Approved VEET No.: 5475	Approved IPART No.: 24143S20-DIYEIJC
212021B 212022B 212504B	YKT5BF1V1-L110	Approved VEET No.: 5475	Approved IPART No.: 24143S20-DIYEIJC

- [1] Operating Frequency=50/60Hz
- [2] Switch Times≥20000

