

- Easy installation, even light output.



181003



181004



Microwave motion sensor kits



Sustained emergency kits (LiFePO4 Battery)



White trim D330/D390mm



Chrome trim D330/D390mm

## FEATURES

- Even light output
- High efficiency SMD LED chips
- Powder coated steel base
- Opal high quality diffuser
- 6mm terminal block
- Centered cable entry
- Compatible with 51mm Beza box
- Different trim options available
- Plug and play modular sensor and emergency kit install on-site

## DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

## INCLUDES

- Constant current dimmable LED driver
- Mounting accessories

## APPLICATIONS

- Residential
- Hallways
- Stairwells
- Porches
- Walls ceilings

## WARRANTY

- Five years (subject to terms and conditions)

| CERTIFICATION | IP RATING | DIMMABLE                      | TRI-COLOUR | Ra        | DISTRIBUTION | DIMENSIONS(mm)                                                                  |
|---------------|-----------|-------------------------------|------------|-----------|--------------|---------------------------------------------------------------------------------|
|               |           | <br>leading and trailing edge |            | <br>Ra≥80 |              | <br>181003: 95mm height, 330mm diameter<br>181004: 115mm height, 390mm diameter |

| Part No. | Order Code | Model No.            | Voltage  | Watt. | PF  | Color Temp.       | Lumens           | Beam Angle | Lifetime L70B50 | Net Weight (kg) |
|----------|------------|----------------------|----------|-------|-----|-------------------|------------------|------------|-----------------|-----------------|
| 181003   | 181003     | CLF1W-D-D3314        | 220-240V | 14W   | 0.9 | 3000K/4000K/5700K | 1300/1500/1400lm | 120°       | 35000h          | 0.54            |
| 181004   | 181004     | CLF1WTC-D-D3927M 17W | 220-240V | 17W   | 0.9 | 3000K/4000K/5700K | 1450/1600/1500lm | 120°       | 35000h          | 0.75            |
|          |            | CLF1WTC-D-D3927M 27W | 220-240V | 27W   | 0.9 | 3000K/4000K/5700K | 2300/2500/2400lm | 120°       | 35000h          | 0.75            |

[1] Operating Frequency=50/60Hz; [2] Operating Temperature:-20 °C~+40 °C

## Accessorie Spec (Optional)

| Part No. | Order Code | Model No.          | Note                                               |
|----------|------------|--------------------|----------------------------------------------------|
| 183059   | 183059     | ECA1CL             | Sandy oyster diffuser and trim D330mm white        |
| 183079   | 183079     | ECA3CL             | Sandy oyster diffuser and trim D390mm white        |
| 183069   | 183069     | ECA2CL             | Sandy oyster diffuser and trim D330mm satin chrome |
| 183089   | 183089     | ECA4CL             | Sandy oyster diffuser and trim D390mm satin chrome |
| 283049   | 283049     | MA1EN04W005-L11W08 | Sustained emergency kits                           |
| 283059   | 283059     | ECMMSB1            | Microwave motion sensor kits                       |

## 14W Sandy Oyster Dimmer Compatibility List

| Dimmer Brand | Model No. of Dimmer | Mode          | Dimming % |      |
|--------------|---------------------|---------------|-----------|------|
|              |                     |               | Min       | Max  |
| HPM          | 200L                | Leading Edge  | 11%       | 82%  |
| CLIPSAL      | 32E450TM            | Trailing Edge | 11%       | 95%  |
| DIGINET      | MEDM                | Trailing Edge | 0%        | 100% |
| CLIPSAL      | 32E450UDM           | Trailing Edge | 15%       | 98%  |
| Legrand      | Cat-400T            | Trailing Edge | 9%        | 94%  |
| TRADER       | DIMR                | Trailing Edge | 0%        | 88%  |
| CLIPSAL      | 32ELEDM             | Trailing Edge | 4%        | 99%  |
| CABAC        | HNS610DT            | Trailing Edge | 1%        | 94%  |
| CABAC        | HNS620DT            | Trailing Edge | 0%        | 95%  |
| CABAC        | HNS630DT            | Trailing Edge | 1%        | 92%  |

## 27W Sandy Oyster Dimmer Compatibility List

| Dimmer Brand | Model No. of Dimmer | Mode          | Dimming % |      |
|--------------|---------------------|---------------|-----------|------|
|              |                     |               | Min       | Max  |
| CLIPSAL      | 32E450TM            | Trailing Edge | 3%        | 99%  |
| DIGINET      | MEDM                | Trailing Edge | 0%        | 93%  |
| CLIPSAL      | 32E450UDM           | Trailing Edge | 3%        | 99%  |
| Legrand      | Cat-400T            | Trailing Edge | 1%        | 96%  |
| TRADER       | DIMR                | Trailing Edge | 0%        | 88%  |
| CLIPSAL      | 32ELEDM             | Trailing Edge | 0%        | 100% |
| CLIPSAL      | 31E2PUDM            | Trailing Edge | 4%        | 98%  |
| CLIPSAL      | 31E2RUDM            | Trailing Edge | 3%        | 97%  |
| CABAC        | HNS610DT            | Trailing Edge | 0%        | 95%  |