

- Low cost A60 range for downlight.



Budget range
of LED lamps

FEATURES

- High lumen output efficiency
- Edison screw and bayonet cap available
- Low surface temperature for extra safety
- Delivering nearly the same light output as an incandescent bulb
- Long lifetime 15000hrs
- Dimensions are the same as a traditional incandescent bulb

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

APPLICATIONS

- Residential
- Retail
- Cafes
- Restaurants
- Display areas
- Atriums and heritage applications

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
	 leading and trailing edge		

Part No.	Model No.	Voltage	Watt.	PF	CCT.	Cap	Ra	Lumen	Beam Angle	Lifetime L70B50
112073A	YKA60M1-D-11W	220-240V	11W	0.7	3000K	E27	≥80	1055lm	200°	15000h
112074A	YKA60M1-D-11W	220-240V	11W	0.7	3000K	B22	≥80	1055lm	200°	15000h
112081A	YKA60M1-D-11W	220-240V	11W	0.7	6500K	E27	≥80	1167lm	200°	15000h
112082A	YKA60M1-D-11W	220-240V	11W	0.7	6500K	B22	≥80	1167lm	200°	15000h
112115A	YKA60M2-D-14.3W	220-240V	14.3W	0.7	3000K	E27	≥80	1521lm	200°	15000h
112116A	YKA60M2-D-14.3W	220-240V	14.3W	0.7	3000K	B22	≥80	1521lm	200°	15000h
112117A	YKA60M2-D-14.3W	220-240V	14.3W	0.7	4000K	E27	≥80	1670lm	200°	15000h
112118A	YKA60M2-D-14.3W	220-240V	14.3W	0.7	4000K	B22	≥80	1670lm	200°	15000h
112119A	YKA60M2-D-14.3W	220-240V	14.3W	0.7	6500K	E27	≥80	1670lm	200°	15000h
112120A	YKA60M2-D-14.3W	220-240V	14.3W	0.7	6500K	B22	≥80	1670lm	200°	15000h

[1] Operating Frequency=50Hz

[2] Switch Times≥20000

[3] For dimming compatibility please see page 92