



Search



08 9258 8444

Cable

Motors

Dry Treat

Raychem

Heatsrink

Lugs & Terminals

Utilux

[Home](#) / [Shop Online](#) / [Cabling Accessories](#) / [Cable Ties](#) / Cable Ties - Nylon - UV Resistant - Black

[Email Us](#) [Print](#)

Shop Online



Cable Ties - Nylon - UV Resistant - Black

Weather Resistant Nylon Cable Tie

Material: U.L. Approved Nylon 6/6 with added Carbonate 'A'
 Flammability: UL 94V-2, Halogen Free
 Standards: Tensile strength meets or exceeds MIL-S-23190E Standard
 Colour: Black
 Note: * Carbonate A was added for greater resistance to ultra violet in outdoor usage. * Prolongs useful life of cable under sunshine/outdoor application. * Operating Temp: -40C to +85C.

Products		Specification			Related Products				
Part No	Pack Size	Description	Length Mm	Length Inch	Width mm	Max bundle Dia (mm)	Min Tensile Strenght lbs (kgs)	Carton Size	Useage
CV100KW	1000	100 x 2.5mm	100	4"	2.5	25	18 (8)		Minature Size
CV100W	100	100 x 2.5mm	100	4"	2.5mm	25	18 (8)		Minature Size
CV140KW	1000	140 x 3.2mm	142	5 1/25"	3.2	35	40 (18)		Light Duty
CV140W	100	140 x 3.2mm	142	5 1/2"	3.2	35	40 (18)		Light Duty
CV150W	100	150 x 3.6mm	150	6"	3.6	39	40 (18)		Light Duty
CV200KW	1000	203 x 4.6mm	203	8"	4.6	55	50 (22)		Standard Duty
CV200MW	100	203 x 2.5mm	203	8"	2.5	55	18 (8)		Minature Size
CV200W	100	203 x 4.6mm	203	8"	4.6	55	50 (22)		Standard Duty
CV250W	100	250 x 4.8mm	250	10"	4.8	74	50 (22)		Standard Duty
CV292W	100	292 x 3.6mm	292	11 1/2"	3.6	85	40 (18)		Light Duty
CV300SKW	1000	300 x 4.8mm	300	11 13/16"	4.8	85	50 (22)		Standard Duty
CV300SW	100	300 x 4.8mm	300	11 13/16"	4.8	85	50 (22)		Standard Duty
CV300W	100	300 x 7.6mm	300	11 7/8"	7.6	88	120 (55)		Heavy Duty
CV368KW	1000	368 x 4.8mm	368	14 1/2"	4.8	102	50 (22)		Standard Duty
CV368W	100	368 x 4.8mm	368	14 1/2"	4.8	102	50 (22)		Standard Duty
CV380W	100	380 x 7.6mm	380	15"	7.6	110	120 (55)		Heavy Duty
CV450MW	100	450 x 4.8mm	450						
CV450W	100	450 x 8.0mm	450	17 3/4"	8.0	133	175 (80)		Heavy Duty
CV550LW	100	550 x 12.7mm	550						
CV550W	100	550 x 8.0mm	550	21 11/16"	8.0	166	175 (80)		Heavy Duty
CV762W	100	762 x 9.0mm	762	30"	9.0	236	175 (80)		Heavy Duty
CV812W	100	812 x 9.0mm	812	32"	9.0	246	175 (80)		Heavy Duty



