

Product card: ARCA 302015

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws. Door guide included.

Support items:

[Product card \(PDF\)](#)
[Dimensional drawing \(mm\)](#)
[Cad-files \(registration needed\)](#)



Sample photo

Product nbr: 8120002
 Description: Cabinet, PC
 Remarks: Grey cover, 1-point locking, hinges on the long side
 Package: 1
 Unit: PCS
 Product group:
 EAN: 6418074079138
 SSTL number: 3423044
 Electric No. Denmark: 8212091003
 Electric No. Sweden: 2500110
 ETIM: EC000261
 Enclosure/switchgear cabinet (empty)

Dimensions:

Length (mm):	300.0
Width (mm):	200.0
Height (mm):	150.0
Length (inch):	11.8
Width (inch):	7.9
Height (inch):	5.9

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	RAL 7035 -light grey
Gasket material:	Polyurethane

Temperatures:

Temperature °C (short term):	-40 ... 120 °C
Temperature °C (continuous):	-40 ... 80 °C
Temperature °F (short term):	-40 ... 250 °F
Temperature °F (continuous):	-40 ... 175 °F

Ratings:

Ingress Protection (EN 60529):	IP66
Impact Resistance (EN 62262):	IK10 +35°C /IK08 -25°C
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 746C 5V
Glow Wire Test (IEC 695-2-1) °C:	960

Certificates:

[SGS Fimko](#)
[Gost R](#)

Product is connected to following catalogs:

Fibox Enclosures : ARCA IEC : ARCA 302015