



Representative Photo Only
(actual product may vary based on configuration selections)

Metal Retaining Clip For 9674 Base

- Complete range from PCB to power relays to cover all of your switching requirements
- International certifications and approvals including CE, CSA, EAC, PCT, RINA, VDE and RoHS, providing quality assurance of a market leading product
- Compact construction allowing for most efficient use of your space

SPECIFICATIONS

Component Type	Timers and Control relays	Retaining Clip
In, Rated Current		12 A
Icw, Short Time Withstand Current, 10ms (rms)		20 A, 10ms
Un, Nominal Operational Voltage, AC		250 V AC
Ue, Rated Operational Voltage, AC, max		400 V AC
Contact Breaking Capacity, DC1, 30V		12 A
Contact Breaking Capacity, DC1, 110V		0.5 A
Contact Breaking Capacity, DC1, 220V		0.25 A
Rated Load, AC-1		3000 VA
Rated Load, AC-15		700 VA
Contact Rated Power, Single Phase Motor, 230V AC		0.55 kW
Material, Contacts		Silver Nickel (AgNi) material
Electrical Service Life at Un, In		100000 cycles
Mounting		Plug-in
Shock Acceleration (Max.)		20 g
Shock Duration (Max.)		4 ms
Vibration Acceleration (Max.)		17 g
Vibration Frequency, Operational (Max.)		150 Hz
Certifications		CE CSA EAC GOST-R IMQ C-UR-US VDE
Shipping Approvals		Lloyd's Register of Shipping RINA (Registro Italiano Navale)

Catalogue No: **96.71**

METAL RETAINING CLIP FOR 9674 BASE

Timers and Control Relays > General Purpose Relays > Electromechanical Relays > Finder Electromechanical Relays > Power Relays > 56 Series Mini Square Base Relays



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -