



Flexilok® system

Construction: Nylon (PA66) or polypropylene moulded fitting.

- One piece fast fit
- Slim design
- IP rating: IP66
- Anti-vibration and tamper resistant
- Pull off strength with:
 - (FLK21 - FPAS21 25kg)
 - (FLK21 - FPAL21 20kg)
 - (FLK20-PP - FPP20 13kg)
- Can be removed using a screwdriver
- Suitable for fine and coarse pitch conduits
- Temperature range -50°C to +135°C
- Metric threads supplied complete with locknuts
- Low Fire Hazard (LFH), see page 94
- Halogen, sulphur and phosphorus free
- Available in black, grey (RAL 7031) and white, see page 69



FITTINGS

FLK

straight external thread

One piece, slim, fast fit, external threaded fitting suitable for knockouts or threaded entries.



FLK

Push in

Simple, one piece, push in fitting suitable for knockouts with no need for locknuts.



FLK90

90° elbow external thread

One piece, slim, fast fit, external threaded 90 degree elbow fitting suitable for knockouts.



FLK-FLK

coupler

One piece, slim, fast fit coupler for joining 2 conduits together.



european (NW) sizes
nominal size (mm)
OD mm

Ext Metric Ext Metric (PP) Ext PG Ext Metric Ext PG Coupler

7	10	10.0	FLK10-M12*						
7	10								
8	11	11.5							
10	13	13.0	FLK13-M16		FLK13-PG9				
10	13								
10	13								
12	16	15.8	FLK16-M16	FLK16-M16-PP	FLK16-PG11	FLK16-PL20	FLK16-M16-90	FLK16-PG11-90	FLK16-FLK16
12	16		FLK16-M20		FLK16-PG13		FLK16-M20-90		
12	16								
12	16	16.1							
14	18	18.5							
14	18								
	20	20.0	FLK20-M20	FLK20-M20-PP		FLK20-PL20	FLK20-M20-90		FLK20-FLK20
17	21	21.2	FLK21-M20		FLK21-PG16	FLK21-PL20	FLK21-M20-90	FLK21-PG16-90	FLK21-FLK21
17	21								
17	21								
	25	25.0	FLK25-M25	FLK25-M25-PP		FLK25-PL25	FLK25-M25-90		FLK25-FLK25
22	25.4	25.4							
23	28	28.5	FLK28-M25		FLK28-PG21	FLK28-PL25	FLK28-M25-90	FLK28-PG21-90	FLK28-FLK28
23	28								
29	34	34.5	FLK34-M32	FLK34-M32-PP	FLK34-PG29	FLK34-PL32	FLK34-M32-90	FLK34-PG29-90	FLK34-FLK34
29	34								
36	42	42.5	FLK42-M40*						
36	42								
48	54	54.5	FLK54-M50*						
48	54								
56	67	67.0							

ORDERING NOTES

- Specify black or grey (B=Black, G=Grey) eg. FLK20-M20B
- For white version see page 69

* Coming soon

ALSO AVAILABLE

- Push in fitting removal tool - see accessories page 75
- Brass threaded versions

SPECIALS

