

Your Industrial Products solution

APO41 Modular Polyester Boxes Spec Sheet: GE


- A range of eighteen boxes based on 300mm and 185mm modules.
- The bases are made of hot moulded glass fibre reinforced polyester.
 These come complete with M4 threaded inserts for fixing mounting plates.
 Colour light grey RAL7035.


- Color light grey NAL7033.
 A choice of grey polyester covers or clear polycarbonate covers.
 High degree of protection IP67 (opaque cover) & IP66 (clear cover).
 A high impact rating of IK10 against external mechanical impacts.
 Designed for both wall and pole mounting.
 High temperature rating APO enclosures can withstand continuous temperatures up to 70°C (peak temperatures up to 150°C) and the transparent polycarbonate covers resist service temperatures up to 1 transparent polycarbonate covers resist service temperatures up to 120 °C.
- Maintenance-free and corrosion resistant.
- Self-extinguishing, flame retardant, halogen free and UV stabilised.
 Rated insulation voltage Ui = 1000V.
 UL listed and CSA approved.

- Ideally suited for harsh external applications such as mining, shipyards, marine environments, oil installations etc.
 Mounting Plates are 5mm pertinax insulated (MPP) or 2mm Zn plated
- MS (MPST). Sold separately.

Dimensions W x H x D (mm)	Part No.	
558 x 302 x 175	APO41	Enclosure With Opaque cover
302 x 302 x 175	APO41C	Enclosure With Clear Cover
254 x 228	APO41 MPP	Pertinax Insulated Mounting Plate
249 x 249 :	APO41 MPST	Zn Plated MS Mounting Plate







	Dimensions																			
н	В	D	D1	h	ь	d	d1		h1	ь1	e1	Туре	K	M	R			v	w	Z
302	302	175	-	282	282	150-X	-	130	225	260	45	APO41	282	282	306	306	241	313	241	313