



GE  
Lighting



## Halogen Linear High Watt

TU\*K5 1500W 240V R7S 254MM BX GE  
1/10MIH

# 29187

### Product information

Housing in a clear quartz bulb, these halogen floodlighting lamps have a ceramic one-pin cap on each end and can be operated on 230V or 240V mains. Linear halogen lamps provide a powerful light source for compact fittings used for floodlighting, architectural lighting and security. GE's linear halogen lamps are double ended, using the universal R7s cap format, and are available in the two industry standards of 118mm or 78mm, plus longer, higher wattage versions.

## Product data

Cap/Base	R7s
Bulb Shape	Tubular
Bulb Diameter [mm]	10
Maximum Overall Length [mm]	255.5
Net weight per piece [g]	20
Gross weight per piece [g]	40
Brand	General Electric (GE)
Energy efficiency class (EEC)	D

## Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3000
Nominal lumens [lm]	32000
Rated efficacy [lm/W]	21.33333
Rated Life [h]	2000
Nominal power [W]	1500
Weighted energy consumption [kWh/1000h]	1504.1
Nominal lamp voltage [V]	240

## Electrical data

Coil type	C-8
Dimming Capability	Yes

## Logistic data

DUN Code	00043168291873
EAN Code	9004102291879
Pack Quantity	10
Layer quantity	180 EUR, 240 UK
Layer quantity EUR	180
Layer quantity UK	240
Pallet quantity EUR (PC)	2520
Pallet quantity UK (PC)	4080
Outer case size	381 x 124 x 60 (mm)
Product status	Available

## Application areas



Home



Hospitality

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Halogen Lamps Spectrum Catalogue \(PDF\)](#)

[Halogen DEQ and IR™ DEQ Lamps Data sheet \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)