

LESWV1G
LESWV2G
LESWV3G
LESWV4G
LESWV5G
LESWV6G

Cleaning Guide:


Spraying cleaning products directly on to electrical switches or power points (sockets) is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic)


Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

Do not wash the cover plates in water over 60°C.



Leopard Range of Switch Plates

- Switches are rated 250V 16AX/20A and approved to AS/NZS60669-1
- Fits standard Australian wall boxes and mounting accessories that use 84mm mounting centres
- Uses brass tunnel terminals that have the screws backed out for easier installation of cabling. Switches are two way with looping terminal and suit 4 x 1.5mm² cabling with 4.1mm bore
- Slotted head screws for the terminals
- Uses 'Cat Flap' screw covers for IP rating or mounting screws
- Covers, plates and dollies are made from UV stabilised polycarbonate to avoid discolouring to yellow
- Colour: White
- Typical example of size seen below:



Catalogue Number	Description
LESWV1G	Switch Vertical 1 Gang, 16AX/20A 250V~
LESWV2G	Switch Vertical 2 Gang, 16AX/20A 250V~
LESWV3G	Switch Vertical 3 Gang, 16AX/20A 250V~
LESWV4G	Switch Vertical 4 Gang, 16AX/20A 250V~
LESWV5G	Switch Vertical 5 Gang, 16AX/20A 250V~
LESWV6G	Switch Vertical 6 Gang, 16AX/20A 250V~

Certification Number:

GMA-103194-EA-010

GSM Electrical (Australia) Pty Ltd

Level 2/142-144 Fullarton Road, ROSE PARK SA 5067
p: 1300 301 838 f: 1300 301 778 e: service@gsm.com.au
www.gsm.com.au

