



#### Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

## Part No: MC148GY

Description Stranded 21 AWG PACW, 8C, PVC Insulation, PVC Sheath.

Applicable Standards AS/ACIF S008, BS4737-3.30

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as

Suitable Applications intercommunication.


Not suitable for mains connection.

#### **Cable Construction Drawing**

garland MC148



#### **Cable Construction Relative Parts**









Nominal OD (mm):

	Cable Description									
-	Conductor	AWG	Stranding	Area(mm²)	Diameter(mm)	Material				
		21	14/0.2	0.44	0.87	PACW				
	Insulation	Cores: 8 Material: PVC Colour: White, Blue, Red, Black, Yellow, Green, Nominal Thickness (mm): 0.3 Nominal OD (mm): 1.5								
	Sheath	Material Colour : Nominal	: Thickness (mn	PVC Grey n): 0.70						

6.5

With Garland, you are always well connected.







### Industrial / Power / Data / Security / Fibre

# Garland's Pro Series range is the

experts' choice for high quality cables.

Electrical Properties									
Voltage Rat	Voltage Rating			ELV					
Max. Condu	Max. Conductor DC Resistance @ 20°C			$45.2\Omega/\text{km}$					
Min. Insulat	Min. Insulation Resistance @ 20°C			50MΩ.km					
Voltage Tes	Voltage Test: Conductor to core			1.5 kV ac/1min					
Voltage Tes	t: Core to sheath		3.0 kV ac/1min						
Mechanical Properties									
Operating T	Operating Temperature Range			-15 to 70℃					
Max. Recommended Pulling Tension			246N						
Min. Bend R	Min. Bend Radius (install)			65mm					
Approximat	e Mass		6.8kg/1	6.8kg/100m					
Sheath Prin	ting		GARLAND SECURITY CABLE MC148 - 8 X 14/0.20 22AWG - MM/YYYYY - "Mmark"						
Supply Information									
Pack Size	Pack Type	Dimensio	ns	Qty Per Carton	Cartons Per Pallet				
100m	Plastic Reel	10 x 4.5	x 5″						
250m	Wooden Reel	W33 x 2:	1.8cm						
500m	Wooden Reel	W39 x 2:	1.8cm						

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

