



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

### Part No: MC736S


Description	Stranded 24AWG (7/0.2mm) TACW, 36 Cores, PVC Insulation, Aluminium Polyester Tape Overall Screen, Stranded 24AWG (7/0.2mm) TACW Drain Wire, PVC Sheath.
Applicable Standards	AS/CA S-008, UL758, EIA-RS232, AS 1049
Suitable Applications	For use in the communications, industrial and security sectors, This product can be used to interconnect DTE equipment such as Printers, fax's, modems, and consoles.  In the industrial environment, this product can be used to connect instruments and sensors to data loggers, PLC's and other control equipment.  In the security market, this product can be used to connect motion sensors, entry sensors, card readers and door strikes to monitoring units.

Not suitable for direct connection to mains equipment.

#### **Cable Construction Drawing**



## **Cable Construction Relative Parts**





Cable Description					
Conductor	AWG	Stranding	Area(mm²)	Diameter(mm)	Material
	24	7/0.2	0.22	0.6	TACW
Insulation	Cores: Material: Nominal Thickness (mm) Nominal OD (mm):		36 PVC n): 0.28 1.2		

With Garland, you are always well connected.







#### Industrial / Power / Data / Security / Fibre

# Garland's Pro Series range is the experts' choice for high quality cables.

Drain Wire	AWG	Stranding	Area(mm²)	Diameter(mm)	Material
	24	7/0.2	0.22	0.6	TACW
Screen	Material : Al. Polyester Tape		Таре	Coverage: 100%	
Sheath	Material: PVC Colour: Grey(RAL 70 Nominal Thickness (mm): 1.0 Nominal OD (mm): 10.5			946)	

Electrical Properties	
Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	95.3Ω/km
Min. Insulation Resistance @ 20°C	50MΩ.km
Voltage Test: Conductor to core	1.5 kV ac/1min
Voltage Test: Core to sheath	3.0 kV ac/1min
Voltage Test: Shield to sheath	3.0 kV ac/1min

Mechanical Properties	
Operating Temperature Range	-15 to 70°C
Max. Recommended Pulling Tension	554N
Min. Bend Radius (install)	105mm
Approximate Mass	17.2kg/100m
Sheath Printing	<b>©</b> GARLAND DATA CABLE MC736S - AWM 2464 80℃

Supply Information							
Pack Size	Pack Type	Dimensions	Qty Per Carton Car		ons Per Pallet		
500m	Wooden Reel	W56 x 39.4cm	1R				
Document Change Record		Issue	Date	Prepared by	Approved By		
		01	27-11-2012	YDM	Pent		
		Issue	Change				

300V 36 X 7/0.2 24AWG OAS - MM/YYYY - "Mmark"

With Garland, you are always well connected.

Change History

