



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


## Part No: MCP241S

Description	Stranded 19 AWG PACW, Single Twisted Pairs, PP Insulated, Aluminium		
	Polyester Overall Screen, TACW 24AWG Drain Wire, PVC Sheath.		
Applicable Standards	AS/ACIF S008		
	Used for signal transmission and for connection of DTE and other		
Suitable Applications	computer and security devices.		
	Not intended for direct connection to mains power		

#### **Cable Construction Drawing**

### **Cable Construction Relative Parts**









Cable Description
-------------------

Conductor	AWG	Area(mm²)	Stranding	Diameter(mm)	Material	
	19	0.75	24/0.2	1.13	PACW	
	Pairs: 1					
Insulation	Material		PP	PP		
	Colour: Black/White					
	Nominal Thickness (mm): 0.3					
	Nominal OD (mm): 1.9					
Drain Wire	AWG	Area(mm <sup>2</sup> )	Standing	Diameter(mm)	Material	
	24	0.22	7/0.2	0.6	TACW	

With Garland, you are always well connected.







#### Industrial / Power / Data / Security / Fibre

# **Garland's Pro Series** range is the experts' choice for high quality cables.

Screen	Material: Al. Polyester Tape		Coverage: 100%
Sheath	Material :	PVC	
	Colour:	Black	
	Nominal Thickness (mm) :	1.0	
	Nominal OD (mm):	6.0	

Electrical Properties	
Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	26.4Ω/km
Min. Insulation Resistance @ 20°C	1,000M Ω .km
Voltage Test: Core to Core	1.5 kV ac/1min
Voltage Test: Core to Screen	3.0 kV ac/1min

Mechanical Properties	
Operating Temperature Range	-15 to 80℃
Max. Recommended Pulling Tension	104N
Min. Bend Radius (install)	60mm
Approximate Mass	4.5kg/100m
Sheath Printing	<b>©</b> GARLAND LOW VOLTAGE COMPUTER CABLE MCP241S - 18AWG X 1PAIR 80°C - "Mmark"- Batch

Supply Information					
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet	
500m	Wooden Reel	W39 x H21.8cm	1R		

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

