





Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


## Part No: MCP7054SSWA

Description	Stranded 16 AWG PACW, 4 Twisted Pairs, V-90 PVC Insulated, Aluminium Polyester Tape Overall Screen, TACW 22AWG Drain Wire, 5V-90 PVC Bedding, SWA & 5V-90 PVC Sheath.
Applicable Standards	AS/NZS 1125, AS/NZS 3808
Suitable Applications	Instrument and control cable for use in industrial applications including the interconnection of signals between cabinets, consoles, sensors and display panels. Armouring provides additional protection for high risk areas. Can also be used for carrying low bit rate data signals. Not intended for direct connection to mains power.

#### **Cable Construction Drawing**

#### **Cable Construction Relative Parts**









Cable Description						
Conductor	AWG	Area(mm <sup>2</sup> )	Stranding	Diameter(mm)	Material	
	16	1.5	7/0.5	1.5	PACW	
Insulation	Pairs :		4	4		
	Material :		V-90 PVC	V-90 PVC		
	Colour:			Black & white wires form a pair. A number is printed on each pair for identification.		
	Nominal Thickness (mm):		: 0.32	0.32		
	Nominal OD (mm):		2.2	2.2		

With Garland, you are always well connected.







### Industrial / Power / Data / Security / Fibre

# **Garland's Pro Series** range is the experts' choice for high quality cables.

Drain Wire	AWG	Area(mm²)	Standing	Diameter(mm)	Material	
Drain Wire	22	0.343	7/0.25	0.75	TACW	
Screen	Material : Al. Polyester Tape Coverage : 100%					
Bedding	Material:		5V-90 PVC	5V-90 PVC		
	Colour:		Black	Black		
	Nominal Thickness (mm) :		: 0.9	0.9		
	Nominal OD (mm):		10.6	10.6		
Armoured	Material: 0.9mm SWA		Coverage :	Coverage: >90%		
	Material :		5V-90 PVC	5V-90 PVC		
	Colour:		Black	Black		
Sheath	Nominal Thickness (mm) :		: 1.4	1.4		
	Nominal OD (mm):		15.4	15.4		

Electrical Properties	
Max. Conductor DC Resistance @ 20°C	13.6 $\Omega$ /km
Suggest Voltage Rating	110a.c/150d.c

Mechanical Properties	
Operating Temperature Range	-15 to 90℃
Max. Recommended Pulling Tension	823N
Min. Bend Radius (install)	185mm
Approximate Mass	49.0kg/100m

Supply Information						
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet		
500m	Wooden Reel	W80 x H56cm	1R			

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

With Garland, you are always well connected.

