



PRODUCT DATA SHEET

Date of Issue: 14/03/18

Part No: AC500812/12

ARCPlus UltraSoft CAT 2 Switching Jacket

Features

- UltraSoft Flame Retardant Orange 305gsm fabric
- UltraSoft is 88% cotton, 12% high tenacity nylon
- Velcro front closure & mandarin collar
- Velcro tab closure/adjustment on sleeve
- Sewn with Nomex thread
- Garment is NFPA CAT 2 compliant, 12.4 cal/cm2
- Designed to be worn with Bib Trousers AC500912/12 for full body protection
- Standard length 850mm
- Sizes Small 5XL
- Made In Australia



Standards Compliance

- NFPA 70E Electrical Safety in the Workplace compliant CAT 2, ATPV 12.4 cal/cm2
- AS/NZS 1020:1995, The Control of undesirable static electricity
- Oeko-Tex Standard 100 Class II
- AS/NZS 1906.4.2010, High Visibility Material for Safety Garments
- EN ISO11612:2015 Protective Clothing Protect Against Heat & Flame
 A1, A2, B1, C1, E2, F1
- ASTM F1959, Standard Test Method Determining Arc Rating of Materials for Clothing
- ASTM D6413, Standard Test Method for Flame Resistance of Textiles (Vertical Test)

Disclaimer: The information contained in this data sheet is believed to be true at the time of printing. It is up to the user to determine suitability of use, or potential infringement for specific applications.

Guardian Safety 38 Chifley St Smithfield NSW 2164 Ph: 02 9604 8111 Email: sales@guardiansafety.com.au