



## MINING LOAD CENTRE



### STANDARD INCLUSIONS

- Available in either 48P (2 row 24P) or 72P (3 row 24P)
- IP56 Enclosure & door manufactured from 1.6 mm Mild Steel Powder coated X15 Orange,
- Hinged Escutcheon Powder Coated Gloss White
- Bottom only mild steel gland plate supplied as standard. Optional 3mm brass gland plate available
- The top of the load centre is fully sealed with no gland plate
- Can Accommodate multiple brands of din mounted circuit protection including long body RCBO's
- Supplied with Din rails, Earth Bar, Cirlock mounting rail (Cirlock Lockout arms ordered separately)
- Semi recessed chrome plated pad lockable door handle
- Adhesive vinyl sticker Label kit
- Optional Rapid test version available

### ENCLOSURE PLUS GLAND PLATE & ROOF OPTIONAL EXTRA

- 48P – 400H X 600W X 240D, [P/N - HPCLC48P400](#) (\*)
- 72P – 600H X 600W X 240D, [P/N - HPCLC72P600](#) (\*)
- OPTIONAL 3MM BRASS G/PLATE, [P/N - HPCLC3BRASS](#)
- OPTIONAL SLOPING ROOF, [P/N - HPCLCSROOF](#)

### Note

- (\*) 48P. Top din rail fitted with Cirlock mounting rail
- (\*) 72P. Top & middle din rail fitted with Cirlock mounting rail

### CIRLOCK LOCKING ARMS

- Cirlock Locking Arms to suit NHP DINT, [P/N - ALA-M-1](#)
- Cirlock Locking Arms to suit Schneider Acti9, [P/N - ALA-M-12](#)

### EARTH LEAKAGE TEST KITS

#### Active only switching

- 6 Way + Off, [P/N - HPCELT6A](#)
- 11 Way + Off, [P/N - HPCELT11A](#)
- 22 Way + Off, [P/N - HPCELT22A](#)

#### Active & Neutral switching

- 6 Way + Off, [P/N - HPCELT6AN](#)
- 12 Way + Off, [P/N - HPCELT12AN](#)
- 18 Way + Off, [P/N - HPCELT18AN](#)
- 24 Way + Off, [P/N - HPCELT24AN](#)

### INSTRUCTIONS

1. Select **ENCLOSURE & OPTIONAL BRASS G/PLATE & OR SLOPED ROOF**
2. Select **LOCKING ARMS & QTY**
3. Select **EARTH LEAKAGE TEST KIT**
4. Work out Main Switch & Circuit Protection

53 – 55 Enterprise ST, Paget, Mackay QLD 4740. Phone: (07)49985100