

# Data Sheet

## Power Converter 10 to 15A

CAT NO. REPC11015



Product specifications	
<b>Cat No</b>	REPC11015
<b>Supply voltage</b>	230-240V a.c. 50Hz
<b>Max load</b>	2400V (10A)
<b>Plug</b>	10A, fully moulded
<b>Outlet</b>	15A
<b>Rated residual current</b>	30mA
<b>Typical trip time</b>	30ms
<b>Lead</b>	1.0mm flexible heavy duty (10A) - 1.8m with parking clip
<b>RCBO</b>	Type A
<b>Rated</b>	Indoor use only

# Power Converter 10 to 15A

CAT NO. REPC11015



- Ideal for providing temporary mains supply to 15A appliances and power tools requiring power for short durations
- Adapts 10A connection to 15A connection
- 1 x 15A Double pole shuttered outlet for extra safety
- Parking clip to prevent lead unravelling
- Not suitable for use on dedicated, permanently connected caravan sites or construction sites
- RCBO (10A) protection - combines Residual Current Device (RCD), for fast power cut off reducing the risk of electrocution and Miniature Circuit Breaker (MCB) for overload protection

Single product		
Dimensions	Barcode	Weight
150(L) x 134(W) x 189(H)mm	9321001435013	1125g

  

Outer box (Qty 9)		
Dimensions	Barcode	Weight
470(L) x 420(W) x 220(H)mm	9321001435020	10.1kg

HPM Legrand - Australia  
1300 369 777  
www.hpm.com.au  
ABN 31 000 102 661

HPM Legrand - New Zealand  
0800 476 009  
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.