



Sm.distr, IC², surface, 12M, transp.door

VD112TT

Architecture

Fixing mode	surface-mounting
-------------	------------------

Functions

With a pipe-in lead	yes
---------------------	-----

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Main electrical features

Nominal voltage	400 V
-----------------	-------

Cover, door

Cover type	Closed (plain)
Door transparency	full transparent door
Transparent cover or door	yes
Cover type	Door
Door locking	without
Type of door closing	Latch
Door material	Plastic
Door transparent material	Plastic
Door leave	single
Door quantity	1
Identification od protection index	40
Interlockable	no

Materials

RAL colour	RAL 9010 - Pure white
Colour	white
Colour	pure white
Material	Plastic
Enclosure material	plastic
Surface appearance	glossy/matt
Type of surface treatment	untreated

Dimensions

Depth of installed product	91 mm
Internal depth	72 mm
Height of installed product	200 mm
Width of installed product	292,5 mm
Width in division units	12

Installation, mounting

Suitable for outdoor use	no
--------------------------	----

Accessories included

Mounting plate included	no
With lock	no

Equipment

Number of rows	1
Quantity of section in width	1
Can be accessorized	yes
Quantity of rails	1

Standards

GWT Glow wire test	650 °C
--------------------	--------

Safety

Protection class	isol.class II
Protection index IP	IP40
IK protection code against mechanical impacts	IK07
Halogen free	yes
Ultraviolet resistant	no

Use conditions

Operating temperature	-25 40 °C
-----------------------	-----------