



VD101NT

**Sm.distr.,VD/IC<sup>2</sup>,surface,1row,1M,IP30,no terminals,AUS,without door**

#### Technical properties

##### Architecture

Fixing mode	surface-mounting
-------------	------------------

##### Functions

With a pipe-in lead	Yes
---------------------	-----

##### Configuration

Number of modules	1
-------------------	---

##### Main electrical features

Nominal voltage	400 V
-----------------	-------

##### Electric current

Rated current	63 A
---------------	------

##### Dimensions

Depth of installed product	71 mm
Internal depth	72 mm
Height of installed product	163.5 mm
Width of installed product	27.5 mm

##### Cover, door

Type of door closing	non keylock
Interlockable	No
Number of keylock of the door	0
Cover type	Closed (plain)
Transparent cover or door	No

##### Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

##### Installation, mounting

Suitable for outdoor use	No
--------------------------	----

##### Settings

Enclosure type	Distributor empty cabinet
----------------	---------------------------

<b>Equipment</b>	
Number of rows	1
Quantity of section in width	1
Quantity of rails	1
Can be accessorized	Yes
Number of openings for flange plates	0
Extension possible	No
Earthing terminal block	No
Neutral terminal block	No
Signal passing door	Yes
<b>Standards</b>	
European directive WEEE	not concerned
<b>Safety</b>	
IK protection code against mechanical impacts	IK07
Protection index IP	IP30
Protection class	isol.class II
Halogen free	Yes
<b>Use conditions</b>	
Operating temperature	-25...40 °C