

TRIPROOF

Feature packed, rugged indoor/ outdoor LED batten range

TRIPROOF are robust IK08 vandal resistant fittings with a HACCP food grade rating. Models are available with smart technology Intellisensor, or Ecoswitch to minimise waste.

- Tritone warm, neutral & cool colour temperature selection
- Weather resistant UV stabilized polycarbonate body and diffuser
- Stainless steel tamper proof clips for public spaces
- Dual intensity selection with Ecoswitch on some models
- Intellisensor occupancy sensor available on some models
- Up to 3 hour self charging Emergency battery (Ni-Cd) on some models
- 1 & 2m suspension kits available (1m: **TSSKIT-1M** 2m: **TSSKIT-2M**)



Applications

Outdoor, industrial, sports halls, public amenities



IK08
Impact
Rating



120°
Beam
Angle



>80
CRI Colour
Rendering
Index



5yr
Warranty
Fitting Only



1yr
Warranty
Battery Only



50,000hr
Expected
Lifetime



No
Non-
Dimmable



HACCP
Food
Safe

	LENGTH	WATT	LUMEN	lm/W	CCT	IP	SAP CODE	PROD CODE
618mm	Tritone	20W	1850lm 1990lm 1850lm	93lm/W 100lm/W 93lm/W	4000k 5000k 6500K	IP65	2001164	TRIPROOF20W06-TRI
	Tritone Emergency	20W	1850lm 1990lm 1850lm	93lm/W 100lm/W 93lm/W	4000K 5000K 6500K	IP54	2001165	TRIPROOF20W06-TRI-EM
1215mm	Tritone	20/40W	4090lm 4410lm 4050lm	102lm/W 110lm/W 101lm/W	4000k 5000k 6500K	IP65	2001168	TRIPROOF20/40W12-TRI
	Tritone Emergency	20/40W	4090lm 4410lm 4050lm	102lm/W 110lm/W 101lm/W	4000k 5000k 6500K	IP54	2001066	TRIPROOF20/40W12-TRI-EM
	Tritone Intellisensor	40W	4510lm 3830lm 3350lm	113lm/W 96lm/W 84lm/W	4000K 5000K 6500K	IP65	2001067	TRIPROOF40W12-TRI-SS
	Tritone Intellisensor Emergency	40W	4090lm 4410lm 4050lm	102lm/W 110lm/W 101lm/W	4000K 5000K 6500K	IP54	2001068	TRIPROOF40W12-TRI-SS-EM
	1-10V Dim	40W	3610lm	90lm/W	5000K	IP65	2000670	TRIPROOF40W12-5K-10VDIM
1515mm	Tritone	60W	5600lm 6000lm 5700lm	93lm/W 100lm/W 95lm/W	4000K 5000K 6500K	IP65	2001170	TRIPROOF60W15-TRI

New

New

New

New

New

New

New

