

VISTA EVO

VISTA-EV12-EM

SAP CODE: 2002349


VISTA EVO is a sleek new concept on a traditional design. This well rounded batten may have a small footprint back packs all the features that is expected from a VISTA product. Available in black or white, 2ft or 4ft and optional emergency and motion sensors round out this simple yet reliable LED batten.

APPLICATIONS

Garage, Shed, Offices, Education Facilities, Storage Facilities, Storage Rooms, Manufacturing Facilities, Temporary Installations



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 139.2deg

— C90/270 110.4deg

Photometric diagram shown is for 4000K output.

KEY INFORMATION

Power	20 W 40 W
Lumen Output	2200 / 2300 / 2200 lm 4400 / 4600 / 4400 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	White RAL 9003
IP Rating	IP20
IK Rating	Not Applicable
Operating Ambient Temp.	0 to 40°C
Connection Type	PA14 Terminals
Driver	Integrated
Warranty	5 yrs

PHOTOMETRIC

Efficacy	96 / 105 / 96 lm/W 102 / 110 / 102 lm/W
CCT	4000 / 4700 / 5700 K
CRI	> 80
SDCM	< 5
UGR	< 30
Beam Angle	120°
Flicker-Free	No
Lifespan	>50,000hrs @ Ta 25°C (L70)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Electrical Classification	Class I
Power Charging	1.6 W
Power Standby	3.2 W
Surge Protection	Overload / Short Circuit

EMERGENCY INFORMATION

Test Type	Self-Test
Battery Type	LiFePO4 3.2V
Recharge Time	16 hr
Discharge Time	1.5 hr
Emergency Classification	N/A