

360° SURFACE/FLUSH MOUNT PRESENCE DETECTOR

OS-461P Model No. 55-461

- Security
- Convenience
- Safety
- Energy Saving

FEATURES

- Surface/Flush Mount
- Superior Detection ensures reliable detection
- High performance for optimum switching
- Built in walk test function
- Lens shield included for minimizing or blocking detecting fields

TECHNICAL SPECIFICATIONS

Detection Range: 360° circular, max. Φ7m at 2.5m high

Lux adjustment: 10 Lux to 2000 Lux **Time setting:** 5 sec to 30 min

Operating 0°C to + 45°C (Indoor usage) **Temperature:** -20° to + 45°C (Outdoor usage)

Load Incandescent Lamps: Max. 2000W

HV Halogen Lamps: Max 1000W
LV Halogen Lamps: Max 1000VA
Fluorescent Lamps: Max. 900VA/100µF
Energy Saving Lamp (CFL): 600VA (400W) Max

(includes CFL & PL Lamps)

LED Lamp: Max: 500VA /400W

Dimensions: $111.5 \, \Phi \, x \, 59 \, \text{mm high}$


Protection: Environmental Protection to IP44

Warning!

Warranty void unless installed by a licensed electrician.



















Dual element sensor to detect a small hand waving movement