

OS-465A 360° SENSOR FLUSH MOUNT


Model No. 55-465

FEATURES


- Quad Element Sensor; Equal Sensitivity of Detection from different Directions
- Multi Segmented Lens Shield – Included for minimizing or blocking detection zone
- Easy to Install (Down Light Construction)
- Built in LED Indicator
- Adjustable Time, Distance and Lux
- Available in White only

TECHNICAL SPECIFICATIONS

- Power 240V AC 50Hz
- One Load 10A Max. Voltage Free Contact
 - Incandescent Light 20W - 2300W
 - Halogen Light 240V 20W - 1100W
 - Low Voltage Halogen Light 20W - 300W
 - Fluorescent Light 20W - 400W
 - Energy Saving Lamp (CFL): 600VA (400W) Max
 - LED Lamp: Max: 500VA / 400W
- Environmental Protection to IP40
- 6 Seconds to 12 Minutes Adjustable Shut Off Time
- 360° Detection Range, 6 Metre Diameter at 2.4m High
- 65mm Cut Out



Side View



Top View



Quad element sensor to detect a small hand waving movement




Sensor and Power Box included. Sensor illustrated with Lens Shield.



Three adjustments: Time, Lux, Metre



Fully adjustable Sensor Head



FLUSH mount only 14mm