## **LED SPOTLIGHTS 20W**



55-244



55-247








Description	Colour	Model
LED Spotlight 20W with Motion Sensor	White	55-244
LED Spotlight 20W with Motion Sensor	Black	55-245
LED Spotlight 20W	White	55-246
LED Spotlight 20W	Black	55-247


- Manual override on sensor models only
- Timing & Lux adjustments
- Quick Connect base

- Stainless steel screws
- Polycarbonate ABS construction



## **TECHNICAL DATA**

	Sensor	Non-Sensor
Mounting	Wall/ceiling	Wall/ceiling
Sensor Adjustment	180°	-
Sensor Type	Passive IR	-
Detection Range	22m	-
Detection Angle	240°	-
Time on Adjustment	5 sec to 12 mins	-
Lux Setting (Lux)	0 to 2000	-
Light Intensity (Lumens)	2000	2000
Colour Temperature	5000K	5000K
SMD	GREE	CREE
Voltage	100 to 240V AC 50Hz	100 to 240V AC 50Hz
Operating Temperature	-20° C to +50° C	-20° C to +50° C
Environmental Protection	IP54	IP54



## **LED SPOTLIGHTS 2 x 20W**



55-240 55-243







Description	Colour	Model
LED Spotlight 2 x 20W with Motion Sensor	White	55-240
LED Spotlight 2 x 20W with Motion Sensor	Black	55-241
LED Spotlight 2 x 20W	White	55-242
LED Spotlight 2 x 20W	Black	55-243

- Manual override on sensor models only
- Timing & Lux adjustments
- Quick Connect base

- Stainless steel screws
- Polycarbonate ABS construction

## **TECHNICAL DATA**

	Sensor	Non-Sensor
Mounting	Wall/ceiling	Wall/ceiling
Sensor Adjustment	180°	-
Sensor Type	Passive IR	-
Detection Range	22m	-
Detection Angle	240°	-
Time on Adjustment	5 sec to 12 mins	-
Lux Setting (Lux)	0 to 2000	-
Light Intensity (Lumens)	4000	4000
Colour Temperature	5000K	5000K
SMD	CREE	CREE
Voltage	100 to 240V AC 50Hz	100 to 240V AC 50Hz
Operating Temperature	-20° C to +50° C	-20° C to +50° C
Environmental Protection	IP54	IP54

