



Product Code: MSB604030G

IDE MSB604030G Mild Steel Enclosure Cold Rolled Steel 400W 600H 300D RAL7035 Light Grey IP66

- Rated for 1000 VAC, 1500 VDC
- IP66 protection against dust and water
- Made from durable cold rolled steel
- Single/Double reversible door design
- IK10 impact resistance rating

Specifications

Product Type	Mild Steel Enclosure
Brand	IDE
Ambient Temperature	-25 to 60 deg C
Application	Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts
Cable Entry	125 mm H x 285 mm W
Colour	Light Grey RAL 7035
Degree of Protection	IP66
Depth	300 mm
Door Profiles	2
Door Type	Single/Double Reversible
Finish	Coated with Primer, Hardened Polyester Paint, Textured with UV Protection
Gasket Material	Polyurethane
Height	600 mm
Lock Type	5 mm Double-Bit Lock, (1) 2-Point Lock
Material	Cold Rolled Steel
Maximum Cabinet Load	225 kg
Maximum Door Load	25 kg
Maximum Mounting Plate Load	200 kg
Mounting Plate Size	350 mm H x 570 mm W x 2 mm D
Mounting Type	Surface
NEMA Rating	NEMA 1, 4, 12
Number of Hinges	2
Number of Locks	2
Rated Impact Resistance	IK10
Rated Operational Voltage	1000 VAC, 1500 VDC

Standards and Approvals	Directive 2014/35/EU, IEC 61439-1, IEC 62208, UL 508A
--------------------------------	---

Usable Internal Space	550 mm H x 350 mm W x 279 mm D
------------------------------	--------------------------------

Wall Fixing Dimensions	260 mm H x 260 mm W
-------------------------------	---------------------

Weight	16.2 kg
---------------	---------

Width	400 mm
--------------	--------